

HOPE



HS CODE
63079098
CARTON SIZE / PCS.
60 x 40 x 24 / 10
AET N°2777/10361-03/E04-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16023-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 30 200 15
 LG. KG	1.5 m (connector included) ----- Max. 100 KG
CE	EN 355:2002
MAT.	 PA 12 mm
	45 mm
	 FA 50 101 17 / FA 50 207 55
	NO
+	PPE-R 11.063
	1.86 KG



Largeur de l'absorbeur d'énergie
 Width of the energy absorber
 Ancho del absorbedor de energía
 Larghezza del assorbitor di energia
 Breite des Falldämpfers

LG.



Longueur Poids maxi utilisateur
 Length Max. user weight
 Longitud Peso máximo del usuario
 Lunghezza Peso Max. dell'utente
 Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
 Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
 Material oberes / unteres Verbindungselement



Ouverture
 Gate opening
 Apertura
 Apertura
 Öffnung



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
 Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
 Zugelassen für Arbeiten in der Nähe scharfer Kanten