

FA 60 005 06



FA 60 005 08



FA 60 005 12




FA 60 005 15



FA 60 005 20



FA 60 005 30



HS CODE
63079098
CARTON SIZE / PCS.
FA 60 005 06 : 60 x 40 x 24 cm / 100
FA 60 005 08/12/15/20/30 : 40 x 40 x 24 cm / 50
AET (UE) N°2777/10789-03/E13-01 (FA 60 005 08/12/15/30), N°10789-02/E03-01 (FA 60 005 06/20)
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16017-01/E01-01 AET (UKCA) N°AB0321/16017-01/E03-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 60 005 XX
CE	EN 795:2012 Type B EN 566
	x1
LG.	0.6 m 0.8 m 1.2 m 1.5 m 2.0 m 3.0 m
MAT.	 20 mm PES
R (kN) / MBS (kN)	22 kN / 30 kN
	0.07 kg 0.09 kg 0.13 kg 0.16 kg 0.21 kg 0.33 kg



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)